



| DIA. DASH NO. | GRIP RANGE | ALLFAST PART NO. | L MAX. |
|---------------|------------|------------------|--------|
| -4 | .126/.187 | AF5065-4-1 | .261 |
| | .188/.250 | AF5065-4-2 | .386 |
| | .251/.312 | AF5065-4-3 | .511 |
| | .313/.375 | AF5065-4-4 | .636 |

| DIA. DASH NO. | A | B | C REF. | D | DRILL SIZE | INSTALLATION HOLE SIZE | MINIMUM STRENGTH-LBS | |
|---------------|--------------|--------------|--------|--------------|------------|------------------------|----------------------|---------|
| | | | | | | | SHEAR | TENSILE |
| -4 | .175 .165 | .046 .038 | .750 | .128 .125 | #30 | .1285/.1320 | 200 | 250 |

NOTES:

MATERIAL: SLEEVE-ALUMINUM, STEM-STAINLESS STEEL.

FINISH: SLEEVE-SEE BELOW; STEM-RUST PREVENTIVE OR DRY FILM LUBRICANT.

ORDER PER EXAMPLE:

AF5065 C ()-()

- _____ GRIP DASH IN 1/16THS
- _____ DIAMETER DASH IN 1/32NDS
- _____ FINISH: (-) CHEM FILMED PER MIL-DTL-5541 GOLD
(A) ANODIZED PER MIL-A-8625 DYED RED
(C) CHEM FILMED PER MIL-DTL-5541 CLEAR
- _____ BASIC PART NUMBER

**UNCONTROLLED COPY
WILL NOT BE KEPT UP TO DATE**

| REV. | DATE | BY | E.O. NO. | FASTACK® SC RIVET, BLIND PULL THRU TEMPORARY TACKING FASTENER | PREPARED | CHECKED | APPROVED |
|------|----------|------|----------|---|--------------------|----------|----------------------------|
| NC | 06/25/18 | P.M. | 10253 | | PHILIP MCCURRIE | 06/25/18 | APPROVAL ON FILE |
| | | | | ALLFAST 15200 DON JULIAN ROAD . CITY OF INDUSTRY CA. 91745 PHONE: (626) 968-9388 | AF 5065 | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |