

| PART NUMBER | NOM DIA. | THEO DIA. | A' DIA. MIN. | C MAX. | D DIA. | F DRIVING FLATS | H REF. | J DIA. MAX. | K MAX. | M GAGE PROT. | R RAD. | S MAX. | W GAGE DIA. | HOLE SIZE | BREAK-OFF LIMITS | PREVAILING TORQUE IN. LBS. MIN. | DOUBLE SHEAR STRENGTH LBS. MIN. | TENSILE STRENGTH LBS. MIN. |
|----------------|----------|--------------|--------------|--------|----------------|-----------------|--------|-------------|--------|----------------|--------------|--------|----------------|--------------|------------------|---------------------------------|---------------------------------|----------------------------|
| PLT1000-05-() | .1635 | .332 .325 | .296 | .268 | .1645 .1625 | .086 .081 | .069 | .244 | .267 | .0276 .0238 | .030 .010 | .012 | .2671 .2667 | .168 .165 | +0.020 -0.068 | 1.0 | 3760 | 970 |
| PLT1000-06-() | .1980 | .385 .378 | .342 | .303 | .1990 .1970 | .104 .099 | .077 | .300 | .302 | .0299 .0259 | .030 .015 | .015 | .3147 .3143 | .202 .199 | +0.015 -0.073 | 1.5 | 5240 | 1400 |
| PLT1000-08-() | .2590 | .507 .499 | .463 | .354 | .2600 .2580 | .135 .130 | .102 | .384 | .346 | .0353 .0307 | .030 .015 | .015 | .4245 .4241 | .263 .260 | +0.010 -0.078 | 2.5 | 14600 | 2100 |
| PLT1000-10-() | .3105 | .635 .626 | .577 | .423 | .3115 .3095 | .152 .147 | .134 | .427 | .414 | .0409 .0357 | .040 .020 | .020 | .5389 .5385 | .315 .312 | +0.010 -0.083 | 3.5 | 14600 | 3600 |
| PLT1000-12-() | .3735 | .762 .752 | .696 | .510 | .3745 .3725 | .185 .180 | .160 | .516 | .470 | .0466 .0407 | .040 .020 | .023 | .6532 .6528 | .378 .375 | +0.010 -0.093 | 4.0 | 21000 | 5650 |

| SECOND DASH NUMBER | G GRIP | GRIP RANGE | | L REF. | | | | |
|--------------------|--------|------------|-------|---------|---------|---------|---------|---------|
| | | MIN | MAX | PLT1000 | | | | |
| | | | | -05-() | -06-() | -08-() | -10-() | -12-() |
| - | - | - | - | - | - | - | - | - |
| -02 | .156 | .094 | .156 | .733 | .853 | - | - | - |
| -03 | .219 | .157 | .219 | .795 | .916 | .944 | - | - |
| -04 | .281 | .220 | .281 | .858 | .978 | 1.006 | 1.158 | 1.242 |
| -05 | .344 | .282 | .344 | .920 | 1.041 | 1.069 | 1.221 | 1.304 |
| -06 | .406 | .345 | .406 | .983 | 1.103 | 1.131 | 1.283 | 1.367 |
| -07 | .469 | .407 | .469 | 1.045 | 1.166 | 1.194 | 1.346 | 1.429 |
| -08 | .531 | .470 | .531 | 1.108 | 1.228 | 1.256 | 1.408 | 1.492 |
| -09 | .594 | .532 | .594 | 1.170 | 1.291 | 1.319 | 1.471 | 1.554 |
| -10 | .656 | .595 | .656 | 1.233 | 1.353 | 1.381 | 1.533 | 1.617 |
| -11 | .719 | .657 | .719 | 1.295 | 1.416 | 1.444 | 1.596 | 1.679 |
| -12 | .781 | .720 | .781 | 1.358 | 1.478 | 1.506 | 1.658 | 1.742 |
| -13 | .844 | .782 | .844 | 1.420 | 1.541 | 1.569 | 1.721 | 1.804 |
| -14 | .906 | .845 | .906 | 1.483 | 1.603 | 1.631 | 1.783 | 1.867 |
| -15 | .969 | .907 | .969 | 1.545 | 1.666 | 1.694 | 1.846 | 1.929 |
| -16 | 1.031 | .970 | 1.031 | 1.608 | 1.728 | 1.756 | 1.908 | 1.992 |

| SECOND DASH NUMBER | G GRIP | GRIP RANGE | | L REF. | | | | |
|--------------------|--------|------------|-------|---------|---------|---------|---------|---------|
| | | MIN | MAX | PLT1000 | | | | |
| | | | | -05-() | -06-() | -08-() | -10-() | -12-() |
| -17 | 1.094 | 1.032 | 1.094 | 1.791 | 1.819 | 1.971 | 2.054 | |
| -18 | 1.156 | 1.095 | 1.156 | 1.853 | 1.881 | 2.033 | 2.117 | |
| -19 | 1.219 | 1.157 | 1.219 | 1.916 | 1.944 | 2.096 | 2.179 | |
| -20 | 1.281 | 1.220 | 1.281 | 1.978 | 2.006 | 2.158 | 2.242 | |
| -21 | 1.344 | 1.282 | 1.344 | 2.041 | 2.069 | 2.221 | 2.304 | |
| -22 | 1.406 | 1.345 | 1.406 | 2.103 | 2.131 | 2.283 | 2.367 | |
| -23 | 1.469 | 1.407 | 1.469 | 2.166 | 2.194 | 2.346 | 2.429 | |
| -24 | 1.531 | 1.470 | 1.531 | 2.228 | 2.256 | 2.408 | 2.492 | |
| -25 | 1.594 | 1.532 | 1.594 | 2.291 | 2.319 | 2.471 | 2.554 | |
| -26 | 1.656 | 1.595 | 1.656 | 2.353 | 2.381 | 2.533 | 2.617 | |
| -27 | 1.719 | 1.657 | 1.719 | 2.416 | 2.444 | 2.596 | 2.679 | |
| -28 | 1.781 | 1.720 | 1.781 | 2.478 | 2.506 | 2.658 | 2.742 | |
| -29 | 1.844 | 1.782 | 1.844 | 2.541 | 2.569 | 2.721 | 2.804 | |
| -30 | 1.906 | 1.845 | 1.906 | 2.603 | 2.631 | 2.783 | 2.867 | |
| -31 | 1.969 | 1.907 | 1.969 | 2.666 | 2.694 | 2.846 | 2.929 | |
| -32 | 2.031 | 1.970 | 2.031 | 2.728 | 2.756 | 2.908 | 2.992 | |

▲ "G" TOLERANCE: FOR -05 AND -06 SIZES +.030/-0.010; FOR -08 & -10 SIZES +.040/-0.010; FOR -12 SIZES +.050/-0.010.

MONOGRAM AEROSPACE FASTENERS
a TriMas company
3423 SOUTH GARFIELD AVENUE
COMMERCE, CALIFORNIA 90040
(323) 722-4760 FAX (323) 727-1029

TITLE:
VISU-LOK, FASTENER, BLIND INTERNALLY THREADED, EXTERNAL SLEEVE ALLOY STEEL 100° FLUSH HEAD, SELF LOCKING HIGH STRENGTH

DRAWING NO:
PLT1000-()-()

DRAWN BY: **G.MARTINEZ** DRAWN DATE: **07-25-13**

APPROVED BY: _____ CHECKED DATE: _____

PROPRIETARY AND CONFIDENTIAL:
NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa
CAGE CODE: **5M902**

MONOGRAM
CAGE CODE: **98524**

ECN NO: **14-0694** REV: **G**

ECN DATE: **11/06/14** SHEET 1 OF 2



PROCUREMENT SPEC: ESCBB-2 CLASS I.

MATERIAL: NUT & SCREW: ALLOY STEEL: 4130 PER AMS-S-6758, 4140 PER AMS6382 OR AMS6349 OR 8740 PER AMS6322.

SLEEVE: CORROSION RESISTANT STEEL: 303 OR 304 PER AMS-QQ-S-763, AMS5639 OR AMS5641.

HEAT TREAT: NUT & SCREW: HEAT TREAT PER AMS2759. APPROXIMATELY 180,000 - 200,000 PSI TENSILE (HRC 39-43).

SLEEVE: AS REQUIRED FOR PERFORMANCE.

FINISH: NUT & SCREW: CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 2. CADMIUM PLATE PER NAS 672 IS PERMISSIBLE PROVIDED IT IS FOLLOWED BY A DICHROMATE POST TREATMENT PER AMS-QQ-P-416.



SLEEVE: PASSIVATE PER AMS2700. CADMIUM PLATE PER AMS-QQ-P-416, TYPE I, CLASS 3.


LUBRICANT: LUBRICANTS LISTED BELOW MAY BE APPLIED TO ANY OR ALL COMPONENTS IF REQUIRED FOR PERFORMANCE.



NUT: WWM CARBO-WAX, PARAFFIN WAX AND/OR CETYL ALCOHOL PER AS87132.

SCREW & SLEEVE: DRY FILM LUBE PER AS5272 TYPE I OR MIL-PRF-81329, WWM CARBO-WAX, PARAFFIN WAX AND OR CETYL ALCOHOL PER AS87132.

PART CODE & EXAMPLE: PLT1000 - 05 - 05



GENERAL NOTES:

1. OUTSIDE DIAMETER OF HEAD OF SCREW AND OUTSIDE DIAMETER OF SLEEVE SHALL NOT EXCEED MAXIMUM "D" DIAMETER.
2. CONCENTRICITY OF NUT HEAD CONICAL SURFACE TO "D" DIAMETER SHALL BE WITHIN .005" T.I.R., EXCEPT OVER INDENTATIONS.
3. REMOVE ALL LOOSE OR HANGING BURRS.



LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120° APART ON THE PERIPHERY OF THE NUT COMPONENT AND APPROXIMATELY .040" ABOVE THE INTERSECTION OF THE NUT NOSE ANGLE AND O.D. (MEAN GRIP OF FASTENER).



MANUFACTURER'S IDENTIFICATION:
LETTER "N" DESIGNATES MONOGRAM AEROSPACE FASTENERS.
LETTERS "VS" DESIGNATE VOI-SHAN.

6. HEAD MARKINGS ON NUT DEPRESSED .010" MAX.



THE PRODUCT DESCRIBED BY THIS DRAWING IS "EQUIVALENT TO" AND "INTERCHANGEABLE WITH" THE MANUFACTURER'S PRODUCT LISTED BELOW EXCEPT THE HEAD IDENTIFICATION MARKINGS AND SELF-LOCKING FEATURE. EXISTING STOCK MAY BE REWORKED TO INCORPORATE THE LOCK. WHEN THESE REWORKED FASTENERS ARE SUPPLIED, THE HEAD IDENTIFICATION MAY BE AS SHOWN BELOW:
MONOGRAM...: WF164-WF375 SERIES (MARKING: "N" OVERSTAMPED "L" OR "SL").
VOI-SHAN...: BAAF SERIES (MARKING: "VS", "A", AND "SL").



STANDARD FINISHES AND LUBES ARE SHOWN ABOVE. REFER TO ESCBB-4 FOR SPECIAL FINISHES AND/OR LUBES, IF REQUIRED.



HALF-GRIP SIZES MAY BE ORDERED BY ADDING (.5) TO THE GRIP DASH NUMBERS.

EXAMPLE: PLT1000-06-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 SIXTEENTHS = 0.281".
THE GRIP RANGE FOR THESE HALF-GRIP SIZES WILL BE NOMINAL GRIP +.031"/-.030".
EXCEPT: THE GRIP RANGE FOR -1.5 GRIP SHALL BE MAX GRIP = 0.125", MIN GRIP = 0.078".
THE BASIC "G" DIMENSION WILL BE NOMINAL GRIP +.031" AND THE OVERALL SCREW LENGTH "L" DIMENSION MAY VARY AT MANUFACTURER'S OPTION.



STANDARD GRIP LENGTHS ARE AS TABULATED, SHORTER OR LONGER GRIPS THAN THOSE LISTED MAY BE AVAILABLE AS SPECIALS. ON GRIP LENGTHS SHORTER THAN THOSE LISTED, THE BREAKOFF LIMITS AND PREVAILING TORQUES AS TABULATED DO NOT APPLY.



DISTORTION OF "D" DIAMETER SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MAXIMUM "D" MAX + .001". FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS.



DIMENSIONS "A", "A'", AND "H" ARE FOR ENGINEERING REFERENCE PURPOSES ONLY AND ARE NOT TO BE USED FOR INSPECTION PURPOSES. THESE DIMENSIONS ARE THEORETICAL VALUES DERIVED FROM "D", "S", "V", "W" AND HEAD ANGLE DIMENSIONS.

13. DIMENSIONS ARE EXCLUSIVE OF LUBRICATION.

3423 SOUTH GARFIELD AVENUE
COMMERCE, CALIFORNIA 90040
(323) 722-4760 FAX (323) 727-1029

TITLE:
VISU-LOK, FASTENER, BLIND
INTERNALLY THREADED, EXTERNAL SLEEVE
ALLOY STEEL
100° FLUSH HEAD, SELF LOCKING
HIGH STRENGTH

DRAWING NO:
PLT1000-()-()

DRAWN BY: G.MARTINEZ DRAWN DATE: 07-25-13

APPROVED BY: CHECKED DATE:

PROPRIETARY AND CONFIDENTIAL:
NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa
CAGE CODE:
5M902

MONOGRAM
CAGE CODE:
98524

ECN NO: 14-0694
ECN DATE: 11/06/14

REV: G
SHEET 2 OF 2