

PART NUMBER	NOM DIA.	THEO DIA.	A' DIA. MIN.	C MAX.	D DIA.	F DRIVING FLATS	H REF.	J DIA. MAX.	K MAX.	M GAGE PROT.	R RAD.	S MAX.	W GAGE DIA.	HOLE SIZE	BREAK-OFF LIMITS	PREVAILING TORQUE IN. LBS. MIN	DOUBLE SHEAR STRENGTH LBS. MIN	TENSILE STRENGTH LBS. MIN
PLT1064-05-(-)	.179	.2612 .2564	.241	.315	.180 .178	.086 .081	.033	.244	.300	.0178 .0153	.030 .010	.010	.2195 .2193	.183 .180	+088 -000	1.0	3150	750
PLT1064-06-(-)	.214	.3016 .2966	.270	.350	.215 .213	.104 .099	.036	.300	.333	.0246 .0218	.030 .015	.015	.2440 .2438	.218 .215	+088 -000	1.5	4600	1250
PLT1064-08-(-)	.275	.3948 .3898	.363	.385	.276 .274	.135 .130	.049	.384	.366	.0271 .0242	.030 .015	.015	.3314 .3312	.279 .276	+098 -000	2.5	7900	1900
PLT1064-10-(-)	.326	.4739 .4689	.442	.470	.327 .325	.152 .147	.061	.427	.447	.0296 .0266	.040 .020	.015	.4047 .4045	.330 .327	+103 -000	3.5	11350	3250
PLT1064-12-(-)	.389	.5604 .5554	.529	.555	.390 .388	.185 .180	.071	.516	.527	.0321 .0290	.040 .020	.015	.4854 .4852	.393 .390	+103 -000	4.0	16450	5050

SECOND DASH NUMBER	G GRIP	GRIP RANGE		L REF.				
		MIN	MAX	PLT1064				
				-05-(-)	-06-(-)	-08-(-)	-10-(-)	-12-(-)
-	-	-	-	-	-	-	-	-
-02	.156	.094	.156	.733	.853	-	-	-
-03	.219	.157	.219	.795	.916	.944	1.096	1.180
-04	.281	.220	.281	.858	.978	1.006	1.158	1.242
-05	.344	.282	.344	.920	1.041	1.069	1.221	1.304
-06	.406	.345	.406	.983	1.103	1.131	1.283	1.367
-07	.469	.407	.469	1.045	1.166	1.194	1.346	1.429
-08	.531	.470	.531	1.108	1.228	1.256	1.408	1.492
-09	.594	.532	.594	1.170	1.291	1.319	1.471	1.554
-10	.656	.595	.656	1.233	1.353	1.381	1.533	1.617
-11	.719	.657	.719	1.295	1.416	1.444	1.596	1.679
-12	.781	.720	.781	1.358	1.478	1.506	1.658	1.742
-13	.844	.782	.844	1.420	1.541	1.569	1.721	1.804
-14	.906	.845	.906	1.483	1.603	1.631	1.783	1.867
-15	.969	.907	.969	1.545	1.666	1.694	1.846	1.929
-16	1.031	.970	1.031	1.608	1.728	1.756	1.908	1.992

SECOND DASH NUMBER	G GRIP	GRIP RANGE		L REF.				
		MIN	MAX	PLT1064				
				-05-(-)	-06-(-)	-08-(-)	-10-(-)	-12-(-)
-17	1.094	1.032	1.094	1.791	1.819	1.971	2.054	
-18	1.156	1.095	1.156	1.853	1.881	2.033	2.117	
-19	1.219	1.157	1.219	1.916	1.944	2.096	2.179	
-20	1.281	1.220	1.281	1.978	2.006	2.158	2.242	
-21	1.344	1.282	1.344	2.041	2.069	2.221	2.304	
-22	1.406	1.345	1.406	2.103	2.131	2.283	2.367	
-23	1.469	1.407	1.469	2.166	2.194	2.346	2.429	
-24	1.531	1.470	1.531	2.228	2.256	2.408	2.492	
-25	1.594	1.532	1.594	2.291	2.319	2.471	2.554	
-26	1.656	1.595	1.656	2.353	2.381	2.533	2.617	
-27	1.719	1.657	1.719	2.416	2.444	2.596	2.679	
-28	1.781	1.720	1.781	2.478	2.506	2.658	2.742	
-29	1.844	1.782	1.844	2.541	2.569	2.721	2.804	
-30	1.906	1.845	1.906	2.603	2.631	2.783	2.867	
-31	1.969	1.907	1.969	2.666	2.694	2.846	2.929	
-32	2.031	1.970	2.031	2.728	2.756	2.908	2.992	

▲ "G" TOLERANCE: FOR -05 AND -06 SIZES +.030"/-.010"; FOR -08 & -10 SIZES +.040"/-.010"; FOR -12 SIZES +.050"/-.010".

MONOGRAM AEROSPACE FASTENERS
a TriMas company
3423 SOUTH GARFIELD AVENUE
COMMERCE, CALIFORNIA 90040
(323) 722-4760 FAX (323) 727-1029

TITLE:
VISU-LOK, FASTENER, BLIND INTERNALLY THREADED, EXTERNAL SLEEVE TITANIUM, 75 KSI SHEAR 100° REDUCED FLUSH HEAD, SELF LOCKING 1/64" OVERSIZE

DRAWING NO:
PLT1064(-)(-)(-)

DRAWN BY: G.MARTINEZ DRAWN DATE: 08-12-13

APPROVED BY: CHECKED DATE:

PROPRIETARY AND CONFIDENTIAL: NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa
CAGE CODE:
5M902

MONOGRAM
CAGE CODE:
98524

ECN NO:
14-0721
ECN DATE:
11/09/14

REV:
G
SHEET 1 OF 2



PROCUREMENT SPEC: ESCBB-9 CLASS 1, EXCEPT AS SPECIFIED HEREIN.

MATERIAL: NUT & SCREW: 6AL-4V TITANIUM PER AMS4928 OR AMS4967.
SLEEVE: CORROSION RESISTANT STEEL.

HEAT TREAT: NUT & SCREW: HEAT TREAT PER AMS-H-81200 MAX. HYDROGEN 125 PPM.
SLEEVE: AS REQUIRED FOR PERFORMANCE.


FINISH: \triangle (-) NUT, SCREW: NONE.
SLEEVE: PASSIVATE PER AMS2700.

(L) NUT: ALUMINUM COAT (.0002" - .0007" THICK) PER NAS4006.
SLEEVE: PASSIVATE PER AMS2700 ALUMINUM COAT (.0002" - .0007" THICK) PER NAS4006.
SCREW: NONE.

LUBRICANT: \triangle LUBRICANTS LISTED BELOW MAY BE APPLIED TO ANY OR ALL COMPONENTS IF REQUIRED FOR PERFORMANCE.

DRY FILM LUBE PER AS5272 TYPE I OR MIL-PRF-81329, WWM CARBO-WAX, PARAFFIN WAX AND OR CETYL ALCOHOL PER AS87132.

PART CODE & EXAMPLE:



GENERAL NOTES:

1. OUTSIDE DIAMETER OF HEAD OF SCREW AND OUTSIDE DIAMETER OF SLEEVE SHALL NOT EXCEED MAXIMUM "D" DIAMETER.
 2. CONCENTRICITY OF NUT HEAD CONICAL SURFACE TO "D" DIAMETER SHALL BE WITHIN .005" T.I.R., EXCEPT OVER INDENTATIONS.
 3. REMOVE ALL LOOSE OR HANGING BURRS.
 - \triangle 4. LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120° APART ON THE PERIPHERY OF THE NUT COMPONENT AND APPROXIMATELY .040" ABOVE THE INTERSECTION OF THE NUT NOSE ANGLE AND O.D. (MEAN GRIP OF FASTENER).
 - \triangle 5. MANUFACTURER'S IDENTIFICATION:
LETTER "N" DESIGNATES MONOGRAM AEROSPACE FASTENERS.
LETTERS "VS" DESIGNATE VOI-SHAN.
 6. HEAD MARKINGS ON NUT DEPRESSED .010" MAX.
 - \triangle 7. STANDARD FINISHES AND LUBES ARE SHOWN ABOVE. REFER TO ESCBB-4 FOR SPECIAL FINISHES AND/OR LUBES, IF REQUIRED.
 - \triangle 8. HALF-GRIP SIZES MAY BE ORDERED BY ADDING (.5) TO THE GRIP DASH NUMBERS.
- EXAMPLE: PLT1064-06-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 SIXTEENTHS = 0.281".
THE GRIP RANGE FOR THESE HALF-GRIP SIZES WILL BE NOMINAL GRIP +.031"/-.030".
THE BASIC "G" DIMENSION WILL BE NOMINAL GRIP +.031" AND THE OVERALL SCREW LENGTH "L" DIMENSION MAY VARY AT MANUFACTURER'S OPTION.
- \triangle 9. STANDARD GRIP LENGTHS ARE AS TABULATED, SHORTER OR LONGER GRIPS THAN THOSE LISTED MAY BE AVAILABLE AS SPECIALS. ON GRIP LENGTHS SHORTER THAN THOSE LISTED, THE BREAKOFF LIMITS AND PREVAILING TORQUES AS TABULATED DO NOT APPLY.
 - \triangle 10. DISTORTION OF "D" DIAMETER SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MAXIMUM "D" + .001". FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS.
 - \triangle 11. DIMENSIONS "A", "A'", AND "H" ARE FOR ENGINEERING REFERENCE PURPOSES ONLY AND ARE NOT TO BE USED FOR INSPECTION PURPOSES. THESE DIMENSIONS ARE THEORETICAL VALUES DERIVED FROM "D", "S", "V", "W" AND HEAD ANGLE DIMENSIONS.
 12. DIMENSIONS ARE EXCLUSIVE OF LUBRICATION.

3423 SOUTH GARFIELD AVENUE
COMMERCE, CALIFORNIA 90040
(323) 722-4760 FAX (323) 727-1029

TITLE:
VISU-LOK, FASTENER, BLIND
INTERNALLY THREADED, EXTERNAL SLEEVE
TITANIUM, 75 KSI SHEAR
100° REDUCED FLUSH HEAD, SELF LOCKING
1/64" OVERSIZE

DRAWING NO: PLT1064 () - () - ()	
DRAWN BY: G.MARTINEZ	DRAWN DATE: 08-12-13
APPROVED BY:	CHECKED DATE:

PROPRIETARY AND CONFIDENTIAL:
NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa CAGE CODE: 5M902	MONOGRAM CAGE CODE: 98524	ECN NO: 14-0721 ECN DATE: 11/09/14	REV: G SHEET 2 OF 2
------------------------------	---------------------------------	---	---------------------------