

PART NUMBER	NOM DIA.		A THEO DIA.		A' DIA. MIN.		C MAX.		D DIA.		F FLATS		H REF.		J DIA. MAX.		K REF.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
PLT5124-05-(-)	.1640	4,166	.332 .325	8,43 8,25	.296	7,52	.268	6,81	.1645 .1635	4,18 4,15	.086 .081	2,18 2,06	.069	1,75	.244	6,20	.246	6,25
PLT5124-06-(-)	.2021	5,134	.385 .378	9,78 9,60	.342	8,69	.303	7,70	.2026 .2016	5,15 5,12	.104 .099	2,64 2,52	.077	1,96	.300	7,62	.281	7,14
PLT5124-08-(-)	.2645	6,719	.507 .499	12,88 12,67	.463	11,76	.354	8,99	.2651 .2641	6,73 6,71	.135 .130	3,43 3,30	.102	2,59	.384	9,75	.325	8,25
PLT5124-10-(-)	.3115	7,913	.635 .626	16,13 15,90	.577	14,66	.423	10,74	.3120 .3110	7,93 7,90	.152 .147	3,86 3,73	.134	3,40	.427	10,85	.390	9,91
PLT5124-12-(-)	.3740	9,500	.762 .752	19,35 19,10	.696	17,68	.510	12,95	.3745 .3735	9,51 9,49	.185 .180	4,70 4,57	.160	4,06	.516	13,11	.470	11,94

PART NUMBER	R RAD.		S MAX.		V GAGE DIA.		W GAGE DIA.		BREAK-OFF LIMITS		MINIMUM AVAILABLE GRIP LENGTH	\triangle HOLE SIZE		PREVAILING TORQUE MIN.		DOUBLE SHEAR STRENGTH MIN.		TENSILE STRENGTH MIN.	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm		INCH	mm	IN-LB	Nm	LBS.	N	LBS.	N
PLT5124-05-(-)	.030 .010	0,76 0,25	.012	0,31	.0276 .0238	0,701 0,604	.2671 .2667	6,784 6,774	+0,082 -0,006	+2,09 -0,16	-02	.1680 .1650	4,27 4,19	1.0	0,113	3150	14010	900	4000
PLT5124-06-(-)	.030 .015	0,76 0,38	.015	0,38	.0299 .0259	0,760 0,658	.3147 .3143	7,993 7,983	+0,072 -0,016	+1,83 -0,41	-02	.2060 .2030	5,23 5,16	1.5	0,170	4600	20460	1400	6230
PLT5124-08-(-)	.030 .015	0,76 0,38	.015	0,38	.0353 .0307	0,897 0,780	.4245 .4241	10,782 10,772	+0,072 -0,026	+1,83 -0,66	-03	.2685 .2655	6,82 6,74	2.5	0,282	7900	35140	2100	9340
PLT5124-10-(-)	.040 .020	1,02 0,51	.020	0,51	.0409 .0357	1,039 0,907	.5389 .5385	13,688 13,678	+0,072 -0,031	+1,83 -0,79	-04	.3150 .3120	8,00 7,92	3.5	0,400	11350	50480	3600	16010
PLT5124-12-(-)	.040 .020	1,02 0,51	.023	0,58	.0466 .0407	1,184 1,034	.6532 .6528	16,591 16,581	+0,072 -0,031	+1,83 -0,79	-04	.3780 .3750	9,60 9,52	4.0	0,452	16450	73170	5600	24910

MONOGRAM AEROSPACE FASTENERS
a TriMas company
3423 SOUTH GARFIELD AVENUE
COMMERCE, CALIFORNIA 90040
(323) 722-4760 FAX (323) 727-1029

TITLE:
VISU-LOK® II, FASTENER, BLIND
100° FLUSH TENSION HEAD
NOMINAL DIAMETER - GROUND SHANK
A286 CRES

DRAWING NO:
PLT5124(-)(-)(-)

DRAWN BY: G.MARTINEZ
DRAWN DATE: 08-14-13

APPROVED BY: _____
CHECKED DATE: _____

ECN NO: 14-0770
ECN DATE: 11/15/14

REV: F

SHEET 1 OF 2

PROPRIETARY AND CONFIDENTIAL:
NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa
CAGE CODE:
5M902

MONOGRAM
CAGE CODE:
98524



5 2ND DASH NO.	GRIP RANGE 2			
	GRIP MIN.		GRIP MAX.	
	INCH	mm	INCH	mm
-01	-	-	-	-
-02	.094	2,39	.156	3,96
-03	.157	3,99	.219	5,56
-04	.220	5,59	.281	7,14
-05	.282	7,16	.344	8,74
-06	.345	8,76	.406	10,31
-07	.407	10,34	.469	11,91
-08	.470	11,94	.531	13,49
-09	.532	13,51	.594	15,09
-10	.595	15,11	.656	16,66
-11	.657	16,69	.719	18,26
-12	.720	18,29	.781	19,84
-13	.782	19,86	.844	21,44
-14	.845	21,46	.906	23,01
-15	.907	23,04	.969	24,61
-16	.970	24,64	1,031	26,19

5 2ND DASH NO.	GRIP RANGE 2			
	GRIP MIN.		GRIP MAX.	
	INCH	mm	INCH	mm
-17	1,032	26,21	1,094	27,79
-18	1,095	27,81	1,156	29,36
-19	1,157	29,38	1,219	30,97
-20	1,220	30,98	1,281	32,54
-21	1,282	32,55	1,344	34,14
-22	1,345	34,15	1,406	35,72
-23	1,407	35,73	1,469	37,32
-24	1,470	37,33	1,531	38,89
-25	1,532	38,90	1,594	40,49
-26	1,595	40,50	1,656	42,07
-27	1,657	42,08	1,719	43,67
-28	1,720	43,68	1,781	45,24
-29	1,782	45,25	1,844	46,84
-30	1,845	46,85	1,906	48,42
-31	1,907	48,43	1,969	50,02
-32	1,970	50,03	2,031	51,59



PROCUREMENT SPEC:

PROCUREMENT SPECIFICATION = PLT 5000, CLASS II, TYPE I
 PART NUMBER ASSIGNMENT = PLT 5001
 INSTALLATION AND REMOVAL = PLT 5002
 SPECIAL LUBE AND FINISH = PLT 5003

MATERIAL: NUT, SCREW & SLEEVE: CORROSION AND HEAT RESISTANT STEEL, A286 PER AMS5731, AMS5732, OR AMS5737.

DRIVE NUT: MILD STEEL.

HEAT TREAT: NUT & SCREW: HEAT TREAT TO A CORE HARDNESS OF HRC 30-45


DRIVE NUT & SLEEVE: AS REQUIRED FOR PERFORMANCE.

FINISH: NUT & SCREW: SLEEVE: PASSIVATE PER AMS2700.

DRIVE NUT: CORROSION RESISTANT COATING, COLOR BLACK.

LUBRICANT: SOLID DRY FILM LUBE PER THE CHEMICAL REQUIREMENTS OF AS5272 TYPE I OR EVERLUBE 812 PER MIL-PRF-81329, PARAFFIN WAX OR CETYL ALCOHOL PER AS87132 MAY BE APPLIED TO ANY OR ALL COMPONENTS AS REQUIRED FOR PERFORMANCE. (SEE PLT5003 FOR SPECIAL LUBRICANTS AND FINISHES).

PART CODE & EXAMPLE:



GENERAL NOTES:

- 1. LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120° APART ON THE PERIPHERY OF THE NUT COMPONENT.
- 2. HALF-GRIP SIZES MAY BE ORDERED BY ADDING (.5) TO THE GRIP DASH NUMBERS.
 EXAMPLE: PLT5124-06-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 SIXTEENTHS = 0.281" (7,14mm) AND A GRIP RANGE OF .250" THRU .312" (6,35mm THRU 7,92mm).
- 3. DISTORTION OF "D" DIAMETER SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MINIMUM RECOMMENDED HOLE SIZE. FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS (22.23 NEWTONS).
- 4. GROUND SHANK VISU-LOK II BLIND FASTENERS SHOULD NOT BE USED EXCEPT WITH CONSIDERABLE CAUTION IN APPLICATIONS WHICH EXCEED APPROXIMATELY .0005" INTERFERENCE FIT. GROUND SHANK VISU-LOK II BLIND FASTENERS WILL PERFORM SATISFACTORILY WHEN INSTALLED IN THE TABULATED HOLE SIZES.
- 5. SECOND DASH NUMBER (GRIP RANGE) -17 THROUGH -32 NOT AVAILABLE IN -05 DIAMETER.
- 6. HEAD MARKINGS DEPRESSED .010" (0.254mm MAX.), POSITION OPTIONAL.

3423 SOUTH GARFIELD AVENUE
 COMMERCE, CALIFORNIA 90040
 (323) 722-4760 FAX (323) 727-1029

TITLE:
 VISU-LOK® II, FASTENER, BLIND
 100° FLUSH TENSION HEAD
 NOMINAL DIAMETER - GROUND SHANK
 A286 CRES

DRAWING NO: PLT5124()-()-()	
DRAWN BY: G.MARTINEZ	DRAWN DATE: 08-14-13
APPROVED BY:	CHECKED DATE:

PROPRIETARY AND CONFIDENTIAL: NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
 A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
 B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa CAGE CODE: 5M902	MONOGRAM CAGE CODE: 98524	ECN NO: 14-0770 ECN DATE: 11/15/14	REV: F SHEET 2 OF 2
------------------------------	---------------------------------	---	---------------------------