

PART NUMBER	φ NOM		φ A THEO		φ A' MIN		C MAX		φ D		F WRENCH FLATS		(H)		φ J MAX		(K)		R. R		S MAX	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
PLT5421-05-(-)	.179	4,55	.2612 .2564	6,634 6,513	.241	6,12	.293	7,44	.1800 .1780	4,572 4,521	.086 .081	2,18 2,06	.033	0,84	.244	6,20	.272	6,91	.030 .010	0,76 0,25	.010	0,25
PLT5421-06-(-)	.214	5,44	.3016 .2966	7,661 7,534	.270	6,86	.328	8,33	.2150 .2130	5,461 5,410	.104 .099	2,64 2,51	.036	0,91	.300	7,62	.312	7,92	.030 .015	0,76 0,38	.015	0,38
PLT5421-08-(-)	.275	6,98	.3948 .3898	10,028 9,901	.363	9,22	.379	9,63	.2760 .2740	7,010 6,960	.135 .130	3,43 3,30	.049	1,24	.384	9,75	.351	8,92	.030 .015	0,76 0,38	.015	0,38
PLT5421-10-(-)	.326	8,28	.4739 .4689	12,037 11,910	.442	11,23	.448	11,38	.3270 .3250	8,306 8,255	.152 .147	3,86 3,73	.061	1,55	.427	10,85	.426	10,82	.040 .020	1,02 0,51	.015	0,38
PLT5421-12-(-)	.389	9,88	.5604 .5554	14,234 14,107	.529	13,44	.535	13,59	.3900 .3880	9,906 9,855	.185 .180	4,70 4,57	.071	1,80	.516	13,11	.495	12,57	.040 .020	1,02 0,51	.015	0,38

PART NUMBER	V (GAGE PROTRUSION)		φ W (GAGE)		BREAK-OFF LIMITS		MINIMUM AVAILABLE GRIP LENGTH (TABLE II)	HOLE SIZE		PREVAILING TORQUE MIN		DOUBLE SHEAR STRENGTH MIN		TENSILE STRENGTH MIN	
	INCH	mm	INCH	mm	INCH	mm		INCH	mm	IN-LBS	Nm	LBS	N	LBS	N
PLT5421-05-(-)	.0178 .0153	0,452 0,389	.2195 .2193	5,575 5,570	+0,88 -0,00	+2,24 -0,00	-02	.183 .181	4,65 4,60	1.0	0,113	3800	16900	750	3300
PLT5421-06-(-)	.0246 .0218	0,625 0,554	.2440 .2438	6,198 6,193	+0,88 -0,00	+2,24 -0,00	-02	.218 .216	5,54 5,49	1.5	0,170	5400	24000	1250	5600
PLT5421-08-(-)	.0271 .0242	0,688 0,615	.3314 .3312	8,418 8,412	+0,98 -0,00	+2,49 -0,00	-03	.279 .277	7,09 7,04	2.5	0,282	8900	39600	1900	8400
PLT5421-10-(-)	.0296 .0266	0,752 0,676	.4047 .4045	10,276 10,274	+1,03 -0,00	+2,62 -0,00	-03	.330 .328	8,38 8,33	3.5	0,400	12500	55600	3250	14500
PLT5421-12-(-)	.0321 .0290	0,815 0,737	.4854 .4852	12,329 12,324	+1,03 -0,00	+2,62 -0,00	-04	.393 .391	9,98 9,93	4.0	0,452	17800	79200	5050	22500



APPLICABLE SPECIFICATIONS:
 PROCUREMENT SPECIFICATION: PLT5000, CLASS 2, TYPE III
 PART NUMBER ASSIGNMENT: PLT5001
 INSTALLATION AND REMOVAL: PLT5002
 SPECIAL LUBE AND FINISH: PLT5003

MATERIAL:

NUT AND SCREW: CRES A286 PER AMS5731, AMS5732 OR AMS5737.
 SLEEVE: CRES A286 PER AMS5731, AMS5732 OR AMS5737.
 DRIVE NUT: MILD STEEL.

HEAT TREAT:

NUT AND SCREW: HEAT TREAT TO 30-45 HRC.
 SLEEVE: AS REQUIRED FOR PERFORMANCE.
 DRIVE NUT: AS REQUIRED FOR PERFORMANCE.

FINISH:

NUT AND SCREW: PASSIVATE PER AMS2700.
 SLEEVE: PASSIVATE PER AMS2700.
 DRIVE NUT: CORROSION RESISTANT COATING, COLOR BLACK.

LUBRICATION:

NO CODE (): SOLID DRY FILM LUBRICANT PER THE CHEMICAL REQUIREMENTS OF AS5272 TYPE I OR EVERLUBE 812 PER MIL-PRF-81329, PARAFFIN WAX AND/OR CETYL ALCOHOL PER AS87132 MAY BE APPLIED TO ANY OR ALL COMPONENTS AS REQUIRED FOR PERFORMANCE. (SEE PLT5003 FOR SPECIAL LUBRICANTS AND FINISHES).

EXAMPLE PART NUMBER:




TABLE II				
2ND DASH NO. △	GRIP RANGE			
	GRIP MIN		GRIP MAX	
	INCH	mm	INCH	mm
-02	.094	2.39	.156	3.96
-03	.157	3.99	.219	5.56
-04	.220	5.59	.281	7.14
-05	.282	7.16	.344	8.74
-06	.345	8.76	.406	10.31
-07	.407	10.34	.469	11.91
-08	.470	11.94	.531	13.49
-09	.532	13.51	.594	15.09
-10	.595	15.11	.656	16.66
-11	.657	16.69	.719	18.26
-12	.720	18.29	.781	19.84
-13	.782	19.86	.844	21.44
-14	.845	21.46	.906	23.01
-15	.907	23.04	.969	24.61
-16	.970	24.64	1.031	26.19
-17	1.032	26.21	1.094	27.79
-18	1.095	27.81	1.156	29.36
-19	1.157	29.39	1.219	30.96
-20	1.220	30.99	1.281	32.54
-21	1.282	32.56	1.344	34.14
-22	1.345	34.16	1.406	35.71
-23	1.407	35.74	1.469	37.31
-24	1.470	37.34	1.531	38.89
-25	1.532	38.91	1.594	40.49
-26	1.595	40.51	1.656	42.06
-27	1.657	42.09	1.719	43.66
-28	1.720	43.69	1.781	45.24
-29	1.782	45.26	1.844	46.84
-30	1.845	46.86	1.906	48.41
-31	1.907	48.44	1.969	50.01
-32	1.970	50.04	2.031	51.59

GENERAL NOTES:

1. LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120 ° APART ON THE PERIPHERY OF THE NUT COMPONENT.
2. HALF GRIP SIZES MAY BE ORDERED BY ADDING ".5" TO THE GRIP DASH NUMBER.
 EXAMPLE: PLT5421-06-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 SIXTEENTHS = .281" [7,14 mm] AND A GRIP RANGE OF .250" [6,35 mm] THRU .312" [7,92 mm].
3. DISTORTION OF "ØD" PERMISSIBLE IN LOCKING AREA. DISTORTION OF "ØD" SHALL NOT PREVENT INSERTION OF THE FASTENER INTO A RING GAUGE OF LENGTH EQUAL TO ONE DIAMETER AND DIAMETER EQUAL TO MINIMUM RECOMMENDED HOLE SIZE. FORCE FOR INSERTION SHALL NOT EXCEED FIVE (5) POUNDS [22.23 N].
4. PLT5421-05-() GRIP LENGTH AVAILABILITY LIMITED TO -02 THRU -16.
5. HEAD MARKINGS ON NUT DEPRESSED .010 INCH [0,254 mm] MAXIMUM. POSITION OPTIONAL.
6. DRIVE NUT NOT SHOWN FOR CLARITY OF HEAD MARKINGS.

MONOGRAM AEROSPACE FASTENERS
 a TriMas company
 3423 SOUTH GARFIELD AVENUE
 COMMERCE, CALIFORNIA 90040
 (323) 722-4760 FAX (323) 727-1029

TITLE:
 VISU-LOK® II, FASTENER, BLIND,
 100° REDUCED FLUSH SHEAR HEAD,
 1/64" OVERSIZE DIAMETER, CRES A286

DRAWING NO: PLT5421 () - () - ()	
DRAWN BY: A PEREZ	DRAWN DATE: 12/29/2013
APPROVED BY:	CHECKED DATE:

PROPRIETARY AND CONFIDENTIAL:
 NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUME CUSTODY THEREOF AND AGREES:
 A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.
 B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

Alcoa CAGE CODE: 5M902	MONOGRAM CAGE CODE: 98524	ECN NO: 14-0812	REV: F
		ECN DATE: 11/22/14	SHEET 2 OF 2